

PRODUCT DATASHEET SUN@HOME Orbis Cross

Sun@Home Wall luminaires | Wall Lights with Human Centric Lighting Technology



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	52.000 mA
Inrush current	2.1 A
Power factor λ	> 0.70
Protection class	П
Operating mode	Mains voltage

Photometrical data

Luminous flux	600 lm	
Total luminous flux of contained light sources	800 lm	
Luminous efficacy	60 lm/W	
Color temperature	22005000 K	
Reference control setting of contained light source (Kelvin)	2700 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 95	
Standard deviation of color matching	≤6 sdcm	
Flickering metric (Pst LM)	≤ 1 %	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110°	

Dimensions & Weight

Length	309.00 mm
Width	200.00 mm
Height	106.00 mm
Product weight	770.00 g

HCL SMART Wall UpDown TW

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	10000

Emergency lighting

Integrated test switch	No
------------------------	----

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates	Document name		
PDF	User instruction / safety instructions	SUN@HOME ORBIS CROSS		
PDF	Legal information	SUN@HOME		
PDF	Declarations of conformity	SUN HOME ORBIS CROSS TW		
PDF	Declarations of conformity UKCA	SUNATHOME		
	CAD/BIM files	Document name		
	BIM Step 3D	Sun@Home orbis		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075575936	Folding box	82 mm x 132 mm x 354 mm	873.00 g	3.83 dm ³
4058075575943	Shipping box 8	349 mm x 285 mm x 380 mm	7429.00 g	37.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.