

Cesar Amp

96700057 CESAR AMP S U/D 2L930WB HF ANT

THORN

LED 15W CESA_AMP_930_UD	IP65	IK08			
-------------------------	------	------	---	---	--


Cesar Amp

Cesar Amp a wall mounted, architectural LED luminaire for decorative facade lighting, wide beam distribution. Fixed output LED driver. Class I electrical, IP65, Impact strength: IK08. Housing: die-cast aluminium, powder coated anthracite. Working ambient temperature: -20°C to +40°C. Complete with 3000K LED.


Dimensions: Ø90 x 250 mm
Luminaire input power: 15.3 W
Luminaire luminous flux: 904 lm
Luminaire efficacy: 59 lm/W
Weight: 2.22 kg



TLG_CESA_F_AMP_UD_WB_ANT.jpg



TLG_CESA_M_AMP_S_DWN.wmf



96700057.ltd

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 904 lm
Luminaire efficacy*: 59 lm/W
Colour Rendering Index min.: 90
Correlated colour temperature*: 3000 Kelvin

Chromaticity tolerance (initial MacAdam): 3
Rated useful life (B10)*:
L80 70000 h at 25 °C
Ballast: 1x LED_DRV
Luminaire input power*: 15.3 W
Dimming: FIX
LOR: 1,00 ULOR: 0,50 DLOR: 0,50

This product contains a light source of energy efficiency class F.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting