


ROUNDED

582105.0031.730 | Wall luminaires



Wall luminaires
4051859774686
D 300, H 77

Wall (surface)
anthracite metallic (DB703)



Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base and housing made of corrosion resistant pressure die-cast aluminium, seawater resistant powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Diffuser: matt crystal glass, painted inside, with fixing device. Bezel ring with bayonet fixing. Uniform lighting achieved by the use of LED panel boards. Very easy installation thanks to plug & play connection. Drill hole deviations can be compensated to achieve precise positioning. The large connection compartment on the back for convenient connections is also ideal for through wiring. MultiLumen: 4 steps adjustable luminous flux. Factory setting is the lowest luminous flux. MultiColour: Colour temperature adjustable via switching element for 3000 K (factory setting) and 4000 K.

Product specifications


Diameter D	300 mm
Height H	77 mm
Weight	2.9 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 410 lm 1100 lm 4000 K: 420 lm 1150 lm
System power	3000 K: 10 W 27 W 4000 K: 10 W 27 W
System efficiency	3000 K: 41 lm/W 41 lm/W 4000 K: 42 lm/W 43 lm/W
Glare evaluation UGR (4H 8H)	3000 K: 29,7 33,2 4000 K: 29,8 33,3
Beam angle	down 90°/76°/0°/76° up 90°/90°/0°/90°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	smart+free (Bluetooth)
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	31
Luminaires on B16A fuse	50
Luminaires on C10A fuse	52
Luminaires on C16A fuse	85
Inrush current / Inrush current duration	5 A / 50 µs
CIE Flux Code / CEN Flux Code	19 45 73 61 100
Type of protection	IP 66 ceiling mounting IP 66 wall mounting
Protection class	I
Filament test	960 °C
Impact resistance	IK07
Ambient temperature	-20 °C ... + 50 °C
Safety marks	D-mark
Conformity mark	CE, EAC

ROUNDED

582105.0031.730 | Wall luminaires



Spareparts



982971.002
Replacement LED module

982970.002
Replacement glass