

NECTRA LED PLUS 222MM 2500LM 830 IP44 DALI OPAL WHITE (20W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	517419
Ingress protection:	IP44
Nominal power [W]:	20
Luminous flux [lm]*:	2500
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	PC, aluminium
Colour of the body:	white
Diffuser material:	PMMA

CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.

APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms. Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

NECTRA LED PLUS 222MM 2500LM 830 IP44 DALI OPAL WHITE (20W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	Ring material:	PC
Light source:	LED module	Ring colour:	white
Colour temperature [K]:	3000	Mounting dimensions [mm]:	ø195
Luminous flux [lm]:	2500	Impact resistance:	IK08
Rated power of the luminaire [W]:	22	Ingress protection:	IP44
Diffuser type:	OPAL	Mounting version:	recessed
Supply voltage [V]:	220-240	Working temperature [°C]:	from -10 to +35
DIMM DALI:	yes	DIMM 1-10V:	yes
Frequency [Hz]:	50 - 60	Net weight [kg]:	0.590
Luminous efficacy [lm/W]:	113	CE certificate:	340/2023
Dimensions (H/W/T/S) [mm]:	ø222/70	Warranty [years]:	5
Energy efficiency class:	E	Index:	517419
Electrical protection class:	II	EAN:	5905963517419
Colour rendering index:	>80	Category type:	downlights
SDCM:	≤ 3	Luminaire rated power 0min [W]:	22.70
Power factor:	0.90	AC voltage range [V]:	198 - 264
Beam angle [°]:	96	DC voltage range [V]:	196 - 280
Diffuser material:	PMMA	LED lifespan L70B50 [h]:	80000
Optics material:	aluminium	LED lifespan L80B20 [h]:	55000
Optics:	reflector	LED lifespan L90B10 [h]:	30000
Material of the body:	PC, aluminium	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour of the body:	white	Warranty [years]:	5
		Manual:	Download PDF
		Plik LDT:	Download