


LIGHTSTREAM midi

722287.0031.1.76 | Spotlights



Spotlights
4051859956877
L 516, B 220, H 56

Pole mounting, Universal mounting system
anthracite metallic (DB703)



Clever combination of spotlight and pole luminaire in one. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. With membrane valve as a standard to avoid condensed water. Cover clear single-pane toughened glass, edge printed. Cover screwed to housing. Lens system made of plastic (PMMA). Replaceable LED spot modules according to ZHAGA standards. Symmetrical light distribution. Constant light output (CLO). With NFC programming interface. Pre-assembled connection cable, length 0.5 m. Modular design: Mounting set must be ordered separately.

Product specifications

Length L	516 mm
Width B	220 mm
Height H	56 mm
Weight	4.7 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	14700 lm
System power	93 W
System efficiency	158 lm/W
Glare evaluation UGR (4H 8H)	24,5
Beam angle	55°/55°
Rated life	100000 h (L90/B50)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	7
Luminaires on B16A fuse	11
Inrush current / Inrush current duration	65 A / 160 µs
CIE Flux Code / CEN Flux Code	83 96 99 100 100
Type of protection	IP 66
Protection class	I
Filament test	960 °C
Impact resistance	IK08
Ambient temperature	-20 °C ... + 40 °C
Conformity mark	CE

Accessories



61199.009
Fuse box



982638.003
Junction box H with strain relief.

LIGHTSTREAM midi

722287.0031.1.76 | Spotlights




982977.003



982974.003




982058.000
Wall bracket, 500 mm, uncoated




982058.0031
Wall bracket, 500 mm, anthracite metallic



982086.000
Wall bracket, 1000 mm, uncoated



982086.0031
Wall bracket, 1000 mm, anthracite metallic



982049.000
Pole attachment (double): for spigot 60 mm, unpainted



982049.0031
Pole attachment (double): for spigot 60 mm, anthracite metallic (DB703)



982050.000
Pole attachment (double): for spigot 76 mm, unpainted



982050.0031
Pole attachment (double): for spigot 76 mm, anthracite metallic (DB703)



982524.0031
Adapter set for 4-fold configuration (4 x 90°)



982092.000
Pole clip for pole diameter 95 - 114 mm



982093.000
Pole clip for pole diameter 115 - 135 mm



982591.000
Wall bracket, uncoated



982591.0031
Wall bracket, powder-coated



982588.000
Pole bracket for 2 luminaires, uncoated



982588.0031
Pole bracket for 2 luminaires, powder-coated



982589.000
Pole bracket for 3 luminaires, uncoated



982589.0031
Pole bracket for 3 luminaires, powder-coated



982590.000
Pole bracket for 4 luminaires, uncoated



982590.0031
Pole bracket for 4 luminaires, powder-coated



982562.000
Reducing adapter Ø 60 mm



982983.000
Reducing adapter Ø 42 mm

Modules



982978.0031
Pole attachment for 76 mm spigot.



983117.0031
Mounting bracket

LIGHTSTREAM midi

722287.0031.1.76 | Spotlights



983164.0031
Mounting bracket