

DEECOS P micro

911492.003 | Pendant luminaires



Pendant luminaires
4051859739951
D 60, H 340

pendant
deep black, matt (RAL 9005)




Cylindrical pendant luminaire. Housing: die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Black plastic ring and recessed LED to prevent glare from the side. Best colour rendering index Ra>90. Transparent suspension cable 3 m, can be shortened. High quality converter without flickering and stroboscopic effect.

Product specifications

Diameter D	60 mm
Height H	340 mm
Suspension length LP	3000 mm
Weight	1.11 kg
Light source	LED
Colour temperature	2700 K
Rated luminous flux	1150 lm
System power	16 W
System efficiency	72 lm/W
Glare evaluation UGR (4H 8H)	22,1
Beam angle	52°
Rated life	50000 h (L90/B10)
Colour rendering index (CRI)	92
Colour tolerance	2
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	21
Luminaires on B16A fuse	34
Luminaires on C10A fuse	35
Luminaires on C16A fuse	57
Inrush current / Inrush current duration	4.5 A / 65 µs
CIE Flux Code / CEN Flux Code	92 99 100 100 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK06
Ambient temperature	-20 °C ... + 25 °C
Conformity mark	CE

Accessories



982801.003
Anti-glare honeycomb louvre



982802.010
Diffuser, satinated




982803.013
Reflector flood



982804.023
Wide flood lens



982806.002
White plastic ring for reflector.



982802.000
Diffuser, transparent



982803.003
Reflector spot



982804.013
Medium lens



982805.003
Oval corridor lens



982807.002
White plastic ring for lens.