

item number	width of cable tray (mm)	H (mm)	thickness of metal sheet (mm)	amount of bolts for connection (pcs)	weight (kg/m)
NKZIN 50X62X0.70_S	62	50	0,7	2	0,98
NKZIN 50X125X0.70_S	125	50	0,7	2	1,48
NKZIN 50X250X0.70_S	250	50	0,7	2	2,28
NKZIN 50X62X1.25_S	62	50	1,25	2	1,82
NKZIN 50X125X1.25_S	125	50	1,25	2	2,45
NKZIN 50X250X1.25_S	250	50	1,25	4	3,65
NKZIN 100X125X1.25_S	125	100	1,25	4	3,46
NKZIN 100X250X1.25_S	250	100	1,25	4	4,62
NKZIN 50X62X0.70_F	62	50	0,7	2	1,36
NKZIN 50X125X0.70_F	125	50	0,7	2	1,84
NKZIN 50X62X1.25_F	62	50	1,25	2	2,06
NKZIN 50X250X1.25_F	250	50	1,25	4	4,13
NKZIN 100X250X1.25_F	250	100	1,25	4	5,23



length of cable tray: 2098 mm

product description: Cable trays are usable for tray with maintained functionality in fire.
To secure connections of trays with the integrated coupling it is necessary to use screws NSM 6X10.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
F - Hot Dip Galvanized, zinc-layer 50 - 100 µm
EO - epoxy coating for indoor environment, along the perimeter, 60 µm
EC - epoxy coating for indoor environment, - total paint, 60 µm

sales amount: á 2098 mm

meets the requirements: EN 61537:02

classification: ČSN 73 0895 P 90-R
DIN 4102-12 E 90
STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

storage: EN 60721-3-1

