





Ceiling and wall luminaires
4051859369301
D 460, H 120

Ceiling mounting, Wall (surface)
white



Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface).

Product specifications

Diameter D	460 mm
Height H	120 mm
Weight	2.57 kg
Light source	LED
Colour temperature	4000 K
Rated luminous flux	3350 lm
System power	31 W
System efficiency	108 lm/W
Glare evaluation UGR (4H 8H)	21
Beam angle	down 119° up 180°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	83
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	230 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	65
Luminaires on B16A fuse	104
Luminaires on C10A fuse	65
Luminaires on C16A fuse	104
Inrush current / Inrush current duration	0.17 A
CIE Flux Code / CEN Flux Code	41 71 89 87 100
Type of protection	IP 40
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE, EAC

Spareparts



08-311165.012
Replacement diffuser