

PRODUCT DATASHEET

SMART+ Globe Camera Track & Trace

Smart+ Camera Globe Track & Trace | Outdoor Smart Camera Globe Track & Trace with E27 Base



Areas of application

- Outdoor use (IP44)
- Garages
- Entrance areas

Product benefits

- Easy and quick installation
- Increased perception of safety thanks to high brightness
- The recorded data is saved on the unit's memory card or cloud storage
- High-quality materials

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Built in speaker and alarm siren
- HD Live view camera
- Network protocol: WiFi
- Type of protection: IP44
- Camera has Track and Trace Function to follow peoples movements
- 3 MP camera
- Talk from mobile phone to camera



- Automatic night mode
- Motion sensor with activity schedule
- Auto record of motions (SD card required)

TECHNICAL DATA

Electrical data


Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	II

Photometrical data

Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-

Dimensions & Weight

Length	175.00 mm
Width	197.50 mm
Height	314.00 mm
Product weight	1100.00 g



SMART OUTD WIFI GLOBE CAM
TRACE E27

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Dimmable	No
Mounting type	Surface

Application environment	Outdoor
With light source	No
Holder designation	E27

Sensor

Type of sensor	Motion / Daylight
Sensor controlled switching time	60 s
Detection range of motion sensor	3...7 m
Detection threshold of daylight sensor	0...20 lx

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Maximum bulb wattage: 15 W / Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Number of illuminants	1






EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- No light sources included
- Mounting screws and dowels included
- SD card not supplied
- Compatible with SD card type (SD/SDHC/SDXC)
- SD Class recommended 120-160MB/s
- Minimum card capacity 8GB/Maximum 128GB

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	SMART+ GLOBE CAMERA TRACE
 Legal information	Legal insert I-Outdoor
 Declarations of conformity	SMART OUTD WIFI GLOBE CAM TRACE
 Declarations of conformity UKCA	SMART OUTD WIFI GLOBE CAM TRACE
 Declarations of conformity UKCA	SMART OUTD WIFI GLOBE CAM TRACE E27

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763425	Folding box 1	195 mm x 220 mm x 310 mm	1314.00 g	13.30 dm ³
4058075763432	Shipping box 2	410 mm x 240 mm x 330 mm	3199.00 g	32.47 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.