


1 electromechanical relay 230Vac
4PDT 6A, screw, pluggable

| | |
|--|--|
| Code | XCM4A230 |
| Type | CM4A230 |
| Series | CM |
| Connection terminal | 2.5 mm ² screw |
| Input channels | 1 pluggable |
| Contact type | 4PDT, 4 form C, AgNi |
| Nominal current | 6 A (240 Vac) |
| Continuous current | 12 A |
| Min applicable load | 10 mA / 12 V |
| Operating temperature range | -20...+60°C |
| Input / output isolation | 2.5 kVac / 60 s |
| Protection degree | IP 20 |
| Overvoltage category / pollution degree | II / 2 |
| Status indication | LED "Input" |
| Housing material | UL94V-0 plastic material |
| Dimensions (LxHxD) | 27x75x68 mm |
| Approximate weight | 54 g |
| Mounting information | on a rail, side by side |
| APPROVALS AND MARKINGS | CE |
| ACCESSORIES | |
| Mounting rail (IEC60715/TH35-7.5) | PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB |
| Marking tag | already mounted |
| Plugin jumper | CMB27B (6 poles) |
| Input rated voltage | 230 Vac ±10% |
| Spare part relay | 8904077 |



DESCRIZIONE DEL PRODOTTO

CM4A230 1
electromechanical relay 230Vac 4PDT 6A, screw, pluggable