

# PRODUCT DATASHEET

## L 18 W/4000 K

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



## TECHNICAL DATA

### Electrical data

Nominal wattage	18 W
Construction wattage	18.00 W
Nominal voltage	230 V
Nominal current	0.37 A
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Photometrical data

Luminous flux	1200 lm
Luminous efficacy	66 lm/W
Color temperature	4000 K
Light color	40
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Dimensions & Weight

Overall length	590.00 mm
Length with base excl. base pins/connection	590,00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	78.00 g

### Lifespan

Service life	5000 h
--------------	--------

### Additional product data

Base (standard designation)	G13
Mercury content	4.3 mg

### Country-specific categorizations

ILCOS	FD-18/34/3-E-G13-26/590
Order reference	L 18W/640

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	590.00 mm
Height	26.00 mm

Width	26.00 mm
-------	----------

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321959652	Sleeve 1	605 mm x 28 mm x 27 mm	89.00 g	0.46 dm <sup>3</sup>
4008321959751	Shipping box 25	142 mm x 145 mm x 632 mm	2625.00 g	13.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.