

# CORONA 2 LED BASIC S 3750LM 857 AR2 IP66 I CL. WIRE 0,2M SP10KV 32W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	433917
Ingress protection:	IP66
Rated power of the luminaire [W]*:	32
Luminous flux [lm]*:	3750
Colour temperature [K]:	5700
Colour rendering index:	>80
Electrical protection class:	I
Optics:	AR2
Colour of the body:	grey
Luminous efficacy [lm/W]:	115

## CHARACTERISTICS

LED road lamp with high luminous efficiency and energy-saving integrated LED module. Self-cleaning body made of polypropylene (PP) with fibreglass (FG), handle made of aluminium. The lamp uses directional lens arrays (made of polycarbonate PC). The lamp is characterised by a high IP66 ingress protection rating and mechanical shock resistance. The integrated bracket, which is adjustable in increments of 5 degrees, allows adjustment from: -5° to +15° (top, on pole); -5° to +15° (side, on boom). Supplied with 0.2m H07RN-F cable as standard.

## APPLICATION

Road luminaire suitable for illumination of: streets and communal, local, internal and estate roads, cycle paths, alleys, pavements, car parks, squares, private properties and all open spaces.

## DETAILS


# CORONA 2 LED BASIC S 3750LM 857 AR2 IP66 I CL. WIRE 0,2M SP10KV 32W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	433917	Surge protection [kV]:	2
Rated power of the luminaire [W]:	32	Diffuser material:	PC
EAN:	5905963433917	Diffuser type:	clear
Luminous flux [lm]:	3750	Optics material:	PC
Category type:	street lighting	Material of the body:	PP+15% GF
Luminous efficacy [lm/W]:	115	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	75/175/500
Energy efficiency class:	D	Mounting dimensions [mm]:	fi 64/ fi 78
Colour temperature [K]:	5700	Ingress protection:	IP66
Supply voltage [V]:	230	Mounting version:	Top, on pole / Side, on boom
Colour rendering index:	>80	Lateral surface (SCx) [m2]:	0.016
Frequency [Hz]:	50	Net weight [kg]:	1.160
Electrical protection class:	I	Wire type:	H07RN-F 3x1.5
Optics:	AR2	Warranty [years]:	3
SDCM:	≤ 3	CE certificate:	<a href="#">18/2024</a>
Power factor:	0.99	Manual:	<a href="#">Download PDF</a>

## LIGHT CURVES



Card creation date:15 February 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 18/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)