

QBLOK1202

Single-pole terminal block 12x10mm2, green

| • · | |
|--|---|
| Series | QBLOK |
| Code | QBLOK1202 |
| Type | QBLOK.12/TE |
| HS code | 85369010 |
| Colour | Green |
| TECHNICAL FEATURES | |
| Function/Type | Distribution terminal board |
| Number and rated cross connection | |
| <u>A</u> | |
| В | |
| <u>c</u> | |
| D | - |
| Input A | |
| Rated cross-section | 12 x 10 mm ² |
| Connecting capacity (flexible) | 1.5–10 mm² |
| Connecting capacity (rigid) | 1.5–16 mm² |
| Connecting capacity (with ferrule) | 10 mm ² – WP 100/21 |
| Supply bar dimension | |
| Output B | |
| Rated cross-section | |
| Connecting capacity (flexible) | - |
| Connecting capacity (rigid) | - |
| Connecting capacity (with ferrule) | - |
| Output C | |
| Rated cross-section | _ |
| Connecting capacity (flexible) | _ |
| Connecting capacity (rigid) | _ |
| Connecting capacity (with ferrule) | _ |
| Output D | |
| Rated cross-section | - |
| Connecting capacity (flexible) | _ |
| Connecting capacity (rigid) | _ |
| Connecting capacity (with ferrule) | _ |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 500 V |
| Maximum current (rated cross-section) | 63 A |
| Caliber | B5 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | _ |
| Maximum current (rated cross-section) | _ |
| Section (min-max) | _ |
| Tightening torque value (UL) | _ |
| Short term current allowed (Icw) (value effective for 1s) | |
| Peak current (lpk) | |
| Rated impulse withstand voltage / pollution degree | _ |
| Insulation stripping length | 6 mm |
| Tightening torque value (nom. / max.) | 2 / 2.5 Nm |
| Plastic material | Polyamide UL94V-0 |
| Widht (pitch) | 16 mm |
| Length | 85 mm |
| Height mounted on TH35-7.5/TH35-15 | 33 / 41 mm |
| Height for panel mounting | |
| | |
| | |
| ACCESSORIES | |
| ACCESSORIES Marking | CNU/8/51 (cod. NU0851S) |
| ACCESSORIES Marking Single marking tag | CNU/8/51 (cod. NU0851S) |
| ACCESSORIES Marking Single marking tag Marking tag | |
| ACCESSORIES Marking Single marking tag Marking tag End bracket | - |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type | - BT/3 (cod. BT003) |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type | - BT/3 (cod. BT003) BTO (cod. BT007) |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type | - BT/3 (cod. BT003) |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail | - BT/3 (cod. BT003) BTO (cod. BT007) BTU (cod. BT005) |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail DIN rail according to IEC 60715/TH35 | - BT/3 (cod. BT003) BTO (cod. BT007) BTU (cod. BT005) - |
| ACCESSORIES Marking Single marking tag Marking tag End bracket TH35 screw type TH35 snap-fit type TH35 and G32 snap-fit type Mounting rail | - BT/3 (cod. BT003) BTO (cod. BT007) BTU (cod. BT005) |





QBLOK1202



* IP20 protegtion degree* Marking possible with a CNU/8 or CNU/10 tag* Available in grey, green and blue colors* Selfextinguishing plastic material 1 For more details, refer to the data sheet

DESCRIZIONE DEL PRODOTTO

QBLOK.12/TE Single-pole terminal block 12x10mm2, green