



CALIDO CLICKBEAM mini

742297.002 | Surface mounted projector



Surface mounted projectors
4051859999218
D 50, H 125

Track on ceiling
traffic white, matt (RAL 9016)



LED surface-mounted projector with modern cylindrical design with no visible cooling ribs. Housing: extruded aluminium profile, powder-coated. Cover and lever arm made of plastic. Rotation range: 356°. Swivel range: 90°. Heat resistant plastic ring black. Hybrid optical system with polycarbonate lens and reflector in faceted aluminium for particularly homogeneous lighting. Special Click Beam lens suitable for different beam angles. Adjustable lens position by means of push mechanism to adjust the beam angle. Black front ring to prevent glare from the side. UVA- and IR-free light. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Converter integrated in the adapter. The following accessories can be mounted without use of tools: honeycomb louvre.

Product specifications


Diameter D	50 mm
Height H	125 mm
Weight	240 g
Light source	LED
Colour temperature	2700 K
Rated luminous flux	1350 lm 1500 lm
System power	12 W 12 W
System efficiency	113 lm/W 125 lm/W
Glare evaluation UGR (4H 8H)	19,6 21,3
Beam angle	23° 37°
Rated life	50000 h (L70/B50)
Colour rendering index (CRI)	90
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	33
Luminaires on B16A fuse	53
Luminaires on C10A fuse	53
Luminaires on C16A fuse	85
Inrush current / Inrush current duration	18 A / 3 µs
CIE Flux Code / CEN Flux Code	94 99 100 100 100
Type of protection	IP 20
Protection class	II
Filament test	850 °C
Impact resistance	IK03
Ambient temperature	-20 °C ... + 30 °C
Conformity mark	CE

CALIDO CLICKBEAM mini

742297.002 | Surface mounted projector



Accessories



982448.003
Anti-glare honeycomb louvre