

PRODUCT DATASHEET TOUCH DIM RC

Touch DIM® RC | User interfaces for light management systems



Areas of application

- Wireless control in industry and office areas
- Ceiling or independent installation via LMS CI BOX possible

Product benefits

- Dimming without control line by maintenance-free EnOcean radio technology

Product features

- Radio receiver for batteryless EnOcean radio pushbuttons for 2 lighting groups
- Maximum power input: 1.5 W
- Frequency band: 868.3 MHz
- 2 floating semiconductor relay outputs max. 45 mA/240 V
- Up to 30 transmitters can be trained

TECHNICAL DATA

Electrical data

Nominal wattage	1.50 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Dimensions & Weight

Length	189.00 mm
Mounting hole spacing, length	180,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	96.00 g

Temperatures & operating conditions

Ambient temperature range	0...+50 °C
---------------------------	------------

Capabilities

Dimmable	No
Dimming interface	Touch DIM

Certificates & Standards

Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Suitable for up to 15 QTi DALI ECGs, OTi DALI ECGs or HTi transformers per output

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	User instruction
	User instruction
	User instruction

DOWNLOAD DATA



Certificates



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321031938	Folding box 1	215 mm x 35 mm x 47 mm	134.80 g	0.35 dm ³
4008321031945	Shipping box 25	241 mm x 180 mm x 217 mm	3424.00 g	9.41 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.