


DIDH 8 675 KT V2A GFK (106 160)



Figure without obligation



| Type | DIDH 8 675 KT V2A GFK |
|---|--|
| Part No. | 106 160 |
| Conductor support Rd | 8 mm |
| Material of conductor holder | StSt |
| Length (l1) | 675 mm |
| Insulating clearance (l2) | 590 mm |
| Application note | for elevated leading of the air termination conductor for increasing the separation distance, fixing in a concrete base for wedge mounting |
| Diameter Ø of spacer | 16 mm |
| Colour of spacer | light grey (RAL 7035) • |
| Conductor routing | loose |
| Rod / conductor holder | DEHNgrip |
| Material of spacer | GRP |
| Material factor km | 0.7 |
| Permanent temperature range | -50 °C ... +100 °C |
| Material of fixing bush | Al |
| Type | UV stabilised and weather resistant |
| Max. gust wind speed (base 8.5 kg, holder distance 1100 mm, Al Ø8 mm) | 102 km/h |
| Max. gust wind speed (base 17 kg, holder distance 1100 mm, Al Ø8 mm) | 175 km/h |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 286 g |
| Customs tariff number | 85389099 |
| GTIN | 4013364092938 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Verisons with other spacer bar lengths are available upon request.