

WALL PLUS

WALL-MOUNTED EFFECT LIGHT | 2 NARROW BEAMS

STL22735BR/30



10W


Power

40lm
(20lm/20)lm

Luminous flux

2° / 2°


Beam angle



TECHNICAL SPECIFICATIONS TABLE

Beam angle	2° / 2°
Power factor	0,92
Luminous flux	40lm (20lm/20)
Frequency	50/60Hz
Ingress protection rating (IP)	IP65
CRI (Color rendering index)	80
Power	10W
Correlated color temperature (CCT)	3000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h

Technical Drawing




Graphics

STL22735BR

1m	193lx	0,2m
2m	48lx	0,4m
3m	21lx	0,7m
4m	12lx	0,9m
5m	8lx	1,1m

h, Emax, ø



OTHER INFORMATION

Finishing	White
Color temperature	Warm white
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

↓ IES FILE - STL22735BR/30

↓ MANUAL Wall Plus

↓ SKETCHUP - STELLA - STL22735BR-30 - STL22735PTO-30 - WALL PLUS_PACK.zip

↓ REVIT - STL22735BR_PTO_30.rfa

