


BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM

3600/2500LM 830 IP40 I CL. DALI PRM WHITE 36W/22W

SINGLE SENSOR WITH SWITCH

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP40
Impact resistance:	IK06
Nominal power [W]:	58
Luminous flux [lm]*:	6100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	PRM
Mounting version:	suspended

CHARACTERISTICS

Baris 52 LED IoT is a modern suspended lamp that combines elegant design with advanced technology. The modular design makes it easy to service and the unique suspension system ensures simple installation. Available with mounting box or optional plug-in socket.

IoT characteristics The IoT BT PIR HYT DALI version has: a built-in BT HYT module that allows you to program functions in the Lena Lighting Clue app and control in real time; PIR motion and daylight sensor and DALI driver for dimming the light source.

APPLICATION

The luminaire is dedicated to indoor use. It is used as a source of light for offices requiring focussed eyesight where low UGR and illumination of dark areas (e.g. ceilings) are required. The unique design, energy-efficient LED modules, and the possibility of cooperation with external lighting control systems in the DALI standard dedicate the luminaire to be used in modern office buildings of A+ class, with particular consideration for offices, representative rooms, conference halls, and passageways.

Baris 52 LED DIR/IND Single, as the name suggests, is a single luminaire with a pre-determined length. To create a line of length up to 6 meters without joining the profile and up to 25 meters without joining the diffuser allows version BARIS 52 LED.

BARIS 52 LED DIR/IND IOT BT PIR HYT 1423MM

3600/2500LM 830 IP40 I CL. DALI PRM WHITE 36W/22W

SINGLE SENSOR WITH SWITCH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	932380	Colour of the body:	white
Rated power of the luminaire [W]:	58	DIMM DALI:	yes
EAN:	5905963932380	Diffuser colour:	prismatic
Colour temperature [K]:	3000	Version:	BT PIR HYT DALI
Light source:	LED module	Material of the body:	aluminium
Luminous flux [lm]:	6100	Dimensions (H/W/T/S) [mm]:	1423/69/52
Diffuser type:	PRM	Impact resistance:	IK06
Supply voltage [V]:	220 - 240	Ingress protection:	IP40
Frequency [Hz]:	50 - 60	Mounting version:	suspended
Luminous efficacy [lm/W]:	108	Working temperature [°C]:	from -25 to +35
Energy efficiency class:	F	Net weight [kg]:	2.800
Electrical protection class:	I	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	227/2023
LED lifespan L70B50 [h]:	111500	PZH certificate:	B-BK-60112-0357/2023
LED lifespan L80B20 [h]:	70400	Manual:	Download PDF
LED lifespan L90B10 [h]:	34000	Plik LDT:	Download
Diffuser material:	PC		

LIGHT CURVES

