

# PRODUCT DATASHEET

## BLKH CBO RD BAT 3.2V 1.8Ah 5.8Wh

BULKHEAD COMBO ROUND BATTERY | Spare part solution for BULKHEAD COMBO EMERGENCY KIT



### Areas of application

- Suitable for BULKHEAD COMBO ROUND

### Product features

- Battery technology: LiFePO4


TECHNICAL DATA

Electrical data

Nominal voltage	3,2 V
Protection class	I

Dimensions & Weight

Length	66.00 mm
Width	21.00 mm
Height	19.00 mm
Product weight	44.00 g



BLKH CBO RD BAT 3.2V 1.8AH  
5.8WH

Materials & Colors

Mercury content	0.0 mg
-----------------	--------

Application & Mounting

Ambient temperature range	0...+40 °C
Temperature range at storage	-20...+40 °C
Type of connection	Screwless terminal
Dimmable	No

BATTERY

Type of Battery	LiFePO4
Battery size [GMS]	Others

Certificates & Standards






Standards	CE / CB / UKCA / EAC
-----------	----------------------

Additional product data

Product remark

Available from April 2025

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	BLKH CBO RD EM KIT
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Legal Insert G11231528
	Declarations of conformity	BLKH CBO RD
	Declarations of conformity UKCA	BLKH CBO RD

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854492518	Folding box 1	37 mm x 37 mm x 82 mm	53.00 g	0.11 dm <sup>3</sup>
4099854492525	Shipping box 50	207 mm x 207 mm x 184 mm	2802.00 g	7.88 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.