

PROXIMA LED EVO PLUS 390MM 2350LM 840 DALI (CORR) RCR WHITE (22W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	269950
Ingress protection:	IP65/54
Impact resistance:	IK10
Nominal power [W]:	22
Luminous flux [lm]*:	2350
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	PP
Ring material:	ABS

CHARACTERISTICS

Surface-mounted, round LED ceiling lamp, fitted with an integrated, energy-saving LED features high luminous efficiency and high tightness. Its base and ring are made of UV-resistant plastic. Specially shaped diffuser made of impact-resistant PC provides the frame with the highest degree of impact resistance. This ceiling fixture is also available in the variant with a radio motion sensor and a 3h emergency module with a self-test.

Luminaires of the PLUS variant line are fitted with branded components of recognized global manufacturers. It features extended life and warranty, increased light efficiency and optimal use of electricity (Power Factor).

This ceiling fixture is also available in the following variants:

- with a radio motion sensor,
- with a radio motion sensor and DALI,
- corridor variant with DALI,
- DALI Swich DIMM,
- with 3h emergency module with self-test.

APPLICATION

Surface-mounted luminaire for ceiling or wall mounting is intended for outdoor use as façade lighting, or indoors: in rooms with high humidity and in passageways. Also available in a variant with a radio motion sensor, particularly recommended for use in utility rooms and passageways. It will also work well as a source of general light, also due to its additional decorative effect (distribution of indirect light on the assembly plane).


PROXIMA LED EVO PLUS 390MM 2350LM 840 DALI (CORR) RCR WHITE (22W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	22	Ring colour:	white
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	ø390/110
Colour temperature [K]:	4000	Mounting dimensions [mm]:	165/165
Luminous flux [lm]:	2350	Impact resistance:	IK10
Rated power of the luminaire [W]:	24.40	Ingress protection:	IP65/54
Supply voltage [V]:	220-240	Mounting version:	surface
Diffuser type:	OPAL	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Dimensions of single box [mm]:	100/390/390
Motion sensor:	yes	Net weight [kg]:	1.600
Corridor function:	yes	Warranty [years]:	5
DIMM DALI:	yes	CE certificate:	46/2022
Luminous efficacy [lm/W]:	97	Index:	269950
Energy efficiency class:	E	EAN:	5905963269950
Electrical protection class:	I	Category type:	bulkheads
Colour rendering index:	>80	Product line:	PROXIMA LED EVO PLUS
SDCM:	≤ 3	AC voltage range [V]:	198 - 264
Power factor:	0.90	DC voltage range [V]:	176-280
Max load (RCR) [W]:	400	LED lifespan L70B50 [h]:	128000
Beam angle [°]:	120	LED lifespan L80B20 [h]:	82000
Diffuser material:	PC	LED lifespan L90B10 [h]:	41000
Material of the body:	PP	ETIM class:	EC002892
Colour of the body:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Ring material:	ABS	Warranty [years]:	5
		Manual:	Download PDF
		Plik LDT:	Download

LIGHT CURVES



Card creation date:10 January 2025
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 46/2022



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl