# **DEECOS S mini**


## 742202.004.76 | Surface mounted projector





Surface mounted projectors 4051859820031 D 87, H 214

Track on ceiling, Wall track silver



LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. With adapter for RZB 3-circuit DALI tracks. Suitable for Track on ceiling, Wall track. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

**Product specifications** 

87 mm
214 mm
1.15 kg
LED
3000 K
1950 lm
20 W
98 lm/W
20,7
40°/28°
50000 h (L90/B10)
92
2
Risk group 1
Converter, dimmable
DALI
220 - 240 V / 50 - 60 Hz
21
34
35
57
18 A / 250 μs
95 100 100 100 100
IP 20
1
650°C - 30 seconds
IK06
IK06 25 °C

# **DEECOS S mini**

## 742202.004.76 | Surface mounted projector



### **Accessories**



982370.000 Diffuser, transparent



982371.003 Anti-glare honeycomb louvre



982369.013 Medium lens



982421.002 White plastic ring for lens.



982368.013 Reflector medium



982369.033 Wide flood lens



982419.002 White plastic ring for reflector.



982647.002 Decorative glass opal matt



982370.010 Diffuser, satinated



982369.003 Spot lens



982369.023 Flood lens



982368.003 Reflector spot



982368.023 Reflector flood



982369.043 Oval corridor lens



982368.033 Reflector wide flood



982648.002 Decorative glass opal matt