
ForceLINE Linear







- Powerful and robust IP65 low/high bay suitable for industrial applications
- Mounting brackets supplied as standard for droprod or chain/wire installation (suspension kit not included)
- Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan
- Anti-glare polycarbonate diffuser maximises performance and light output
- Powered by Philips











INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	₽	IK
230V	50Hz	-20°C to 25°C	L70 51,000	Ra 80	5	105°	1	IP65	IK09

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	А	TRADE
AFLLED2	Cool White - 600mm	150W	40001/	16500lm	110lm	600mm	£244.00
AFLLED4	Cool White - 1200mm	240W	4000K	31000lm	130lm	1200mm	£422.00

CODE (OPTIONS)	DESCRIPTION	TRADE
/M3	Emergency	+ £90.00
/SM3	Self-Test emergency	+ £121.00
/DM3	DALI emergency	+ £205.00

CODE (OPTIONS)	DESCRIPTION	TRADE
/DD	Digital Dimming (AFLLED2 DD3/DD4) (AFLLED4 DD4)	+ £95.00
/MWS	Integral Microwave Sensor	+ £83.00
/0СТО	OCTO Smart Control	+ £195.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AZLED/MWSP	High Bay Microwave Sensor Programmer	£55.50
* AZLED/MWSP required to program	nme on site. This product is no longer supplied with an inbuilt dipswitch.	