

AKSK2/1

Kala 600mm Suspension Kit (with driver)



Accessory for Kala

Technical Specifications:

Colour / Finish | [White]

Material | [Stainless Steel]

Dimmable | Yes

Dimmable Type | [Mains (Triac)]

IP Rating | IP20

Mounting Option | [Suspended]

Class Protection | 1

Internal / External | Internal

OCTO Category | OCTO options available

Warranty (Years) | 5
CE Mark | Yes
UKCA Mark | Yes
Diameter | 280
Height | 46
RAL Colour | 9,016
Standard Product | Yes
Wattage | 45W
Lumens Delivered | 4800lm (4000K)
Lumens Delivered Category | 3501-5000lm
lm/W | 120lm/W
lm/W Category | [>120lm/W]
Beam Angle | 110
Input | 220/240V
Hertz | 50/60Hz
Operating Temp | -10°C - 45°C
SDCM | 6
UGR | 28
UGR Category | [UGR>19]
Inrush Current | 31A 410us
Running Current | 1050mA
Lumen Depreciation | L80 50,000h
Lumen Depreciation L70 B50 | L70 B50 60,000h
Lumen Depreciation L80 | L80 54,000h
Lumen Depreciation L90 | L90 51,000h

Technical Data - ETIM - Electrical accessories for luminaires (EC002556)

Type of accessory	Other
-------------------	-------

Number of cores	0
-----------------	---

Datasheet generated from <https://onetimepim.com> last updated Friday, February 16, 2024 4:47:48 PM