



CorePro LEDcapsule MV

CorePro LEDcapsule 3.5-40W ND G9 827 G

The LED specialties deliver a high quality light to make themselves to be a true replacement of halogen specialty lamp (such as G9 and R7S). It is particularly suit for task lighting in hotel and restaurants, and ideal for decorative and ambient application. LEDspecialty products deliver huge energy saving and minimize maintenance costs, without any compromise on light quality.

Product data

General Information	
Cap-Base	G9 [G9]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	10000 h
Switching Cycle	5000X
Technical Type	3.5-40W
Light Technical	
Color Code	827 [CCT of 2700K]
Luminous Flux (Nom)	380 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	108.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	3.5 W


Lamp Current (Nom)	17.5 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Ambient (Max)	35 °C
T-Ambient (Min)	-20 °C
T-Case Maximum (Nom)	100 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Capsule
Approval and Application	
Suitable For Accent Lighting	No

CorePro LEDcapsule MV

Energy Consumption kWh/1000 h	4 kWh
Product Data	
Full product code	871869973506700
Order product name	CorePro LEDcapsule 3.5-40W ND G9 827 G
EAN/UPC - Product	8718699735067
Order code	929002326502

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	929002326502
Net Weight (Piece)	0.010 kg


Dimensional drawing




R7S & G9 DOB ND EU/GMGC/LATAM GLASS

Product	D	C
CorePro LEDcapsule 3.5-40W ND G9 827 G	14.5 mm	60 mm


Photometric data



LEDcapsule G9



LEDcapsule 3,5W G9 827





Page 11

LEDcapsule 3,5W G9 827

CorePro LEDcapsule MV

Lifetime



10K

10K

