FLAT SLIM disc


312638.002.76 | Ceiling and wall luminaires





Ceiling and wall luminaires 4051859773900 D 380, H 75

Ceiling mounting, Wall (surface) traffic white, matt (RAL 9016)



Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Glass fastening: bayonet fixing. Uniform lighting achieved by the use of LED panel boards. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. The large connection compartment on the back for convenient connections is also ideal for through wiring. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting is 3000 K. Dimmable DALI.

Product specifications

Product specifications		
Diameter D	380 mm	
Height H	75 mm	
Weight	2.73 kg	
Light source	LED	
Colour temperature	3000 K 4000 K	
	3000 K: 1150 lm 2450 lm	
Rated luminous flux	4000 K: 1150 lm 2500 lm	
	3000 K: 11 W 24 W	
System power	4000 K: 11 W 24 W	
	3000 K: 105 lm/W 102 lm/W	
System efficiency	4000 K: 105 lm/W 104 lm/W	
Glare evaluation UGR (4H 8H)	3000 K: 18,4 21,1 4000 K: 18,4 21,1	
	down 116°	
Beam angle	up 130°	
Rated life	50000 h (L90/B50)	
Colour rendering index (CRI)	80	
Colour telidering index (Citi)	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter, dimmable	
Control	DALI	
Voltage	220 - 240 V / 50 Hz, 60 Hz	
Luminaires on B10A fuse	31	
Luminaires on B16A fuse	50	
Luminaires on C10A fuse	52	
Luminaires on C16A fuse	85	
Inrush current / Inrush current duration	5 A / 50 μs	
CIE Flux Code / CEN Flux Code	44 75 93 79 100	
Type of protection	IP 65	
Protection class	I 03	
Filament test	960 °C	
Impact resistance	IK03	
Ambient temperature	-25 °C + 35 °C	
Safety marks	-25 °C + 35 °C D-mark	
Conformity mark	CE, EAC	

FLAT SLIM disc

312638.002.76 | Ceiling and wall luminaires



Spareparts



982971.002 Replacement LED module



982902.002 Replacement glass