

## PRODUCT DATASHEET

# SubstiTUBE T5 HF HO49 26 W/6500 K 1463.00 mm

SubstiTUBE TUBE T5 HF | LED tubes for electronic high frequency control gears



### Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Offices, public buildings
- Supermarkets and department stores
- Industry

### Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- High luminous flux for sophisticated lighting tasks
- Also suitable for operation at low temperatures

### Product features

- Retrofit replacement of existing T5 lamps on HF ballast installations
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- High color consistency:  $\leq 5$  sdcn



- Lifetime up to 50,000 h
- Low flicker according to EU 2019-2020 ( $SVM \leq 0.4$  /  $PstLM \leq 1$ )
- Type of protection: IP20
- Compatible with many common electronic control gears (see also compatibility list)

## TECHNICAL DATA

### Electrical data

|                           |               |
|---------------------------|---------------|
| Nominal wattage           | 26 W          |
| Construction wattage      | 26.00 W       |
| Nominal voltage           | 80...110 V    |
| Operating mode            | HF (ECG mode) |
| Nominal current           | 177 mA        |
| Type of current           | AC            |
| Inrush current            | 25 A          |
| Operating frequency       | 25...70 kHz   |
| Mains frequency           | 25...70 kHz   |
| Total harmonic distortion | < 20 %        |
| Power factor $\lambda$    | > 0.90        |


### Photometrical data

|   |               |
|---|---------------|
| Luminous flux                           | 4000 lm       |
| Luminous efficacy                       | 153 lm/W      |
| Lumen main.fact.at end of nom.life time | 0.70          |
| Light color (designation)               | Cool Daylight |
| Color temperature                       | 6500 K        |
| Color rendering index Ra                | 83            |
| Light color                             | 865           |
| Standard deviation of color matching    | ≤5 sdcn       |

### Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 190 °    |
| Warm-up time (60 %) | < 2.00 s |
| Starting time       | < 0.5 s  |

### Dimensions & Weight



|                |            |
|----------------|------------|
| Overall length | 1463.00 mm |
|----------------|------------|

|                  |          |
|------------------|----------|
| Diameter         | 17.00 mm |
| Maximum diameter | 17 mm    |
| Product weight   | 192.00 g |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+45 °C |
| Maximum temperature at tc test point | 66 °C        |

### Lifespan

|  |        |
|--|--------|
| Number of switching cycles                   | 200000 |
| Lumen maintenance at end of service lifetime | 0.70   |
| Rated lamp survival factor at 6,000 h        | ≥ 0.90 |

### Additional product data

|                             |         |
|-----------------------------|---------|
| Base (standard designation) | G5      |
| Mercury content             | 0.0 mg  |
| Design / version            | Frosted |

### Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|  |                 |
|--|-----------------|
| Energy efficiency class                      | D               |
| Energy consumption                           | 29.00 kWh/1000h |
| Type of protection                           | IP20            |
| Standards                                    | CE              |
| Photobiological safety group acc. to EN62778 | RG0             |

### Country-specific categorizations

|                 |                 |
|-----------------|-----------------|
| Order reference | RL-T5 49 26W/86 |
|-----------------|-----------------|

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015

|   |              |
|---|--------------|
| Light source cap-type (or other electric interface) | G5           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Length  | 1463.00 mm   |

|          |          |
|----------|----------|
| Height   | 17.00 mm |
| Width    | 17.00 mm |
| EPREL ID | 642865   |

### Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Not suitable for emergency lighting.

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008597202605 | Sleeve<br>1                  | 1,465 mm x 20 mm x 24 mm             | 218.00 g     | 0.70 dm <sup>3</sup>  |
| 4008597602603 | Shipping box<br>10           | 1,518 mm x 153 mm x 80 mm            | 2699.00 g    | 18.58 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

- For current information see [www.ledvance.com/osram-substitute](http://www.ledvance.com/osram-substitute)

### Legal advice

- When used to replace a T5 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.