

QUEST 2 LED M 3600LM DALI I CL. IP66 840 SP10KV (27W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	697364
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	27
Luminous flux [lm]*:	3600
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

High-quality floodlight with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass. It is equipped with directional lens matrices with 3 different light distributions: symmetrical (120°), asymmetric narrow ASN and asymmetric wide ASW. Non-corrosive mounting bracket allowing for adjustment angles between -140° to +185°. The luminaire is available in 2 sizes: M and L. Standard equipped with 0.1m long H07RN-F cable and IP66 quick connector. Wide range of accessories available: protective net, grip for the lighting pole, wall bracket.

APPLICATION

The fitting is dedicated for lighting elevations and billboards.


QUEST 2 LED M 3600LM DALI I CL. IP66 840 SP10KV (27W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	27	Dimensions (H/W/T/S) [mm]:	321/424/37
Index:	697364	Impact resistance:	IK09
Colour temperature [K]:	4000	Ingress protection:	IP66
Light source:	LED	Mounting version:	surface
Luminous flux [lm]:	3600	Working temperature [°C]:	from -20 to +35
Supply voltage [V]:	220 - 240	Lateral surface (SCx) [m2]:	0.140
DIMM DALI:	yes	Net weight [kg]:	4.200
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Beam angle [°]:	120	LED lifespan L70B50 [h]:	125000
Version:	M	LED lifespan L80B20 [h]:	79000
Luminous efficacy [lm/W]:	133	LED lifespan L90B10 [h]:	38000
Energy efficiency class:	D	Cable length [m]:	0.90
Electrical protection class:	I	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	Mark D:	yes
SDCM:	≤ 3	Additional accessories:	protective grid, pole mount, wall mount
Light distribution type:	symmetric 120°	The number of implement units:	1
Surge protection [kV]:	10	Warranty [years]:	5
Diffuser material:	glass	CE certificate:	86/2021
Diffuser type:	transparent	PZH certificate:	B-BK-60212-0480/21
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	anthracite grey	Plik LDT:	Download

LIGHT CURVES




QUEST 2 LED M 3600LM DALI I CL. IP66 840 SP10KV (27W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
559938	QUEST PLUS LED M/L wall holder RAL9006
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016
965913	QUEST 2 LED M/L MAX wall mount RAL7016
567728	QUEST 2 LED M/L Pole holder




QUEST PLUS LED M/L wall holder
RAL9006 (559938)




QUEST 2 LED M - recessed
frame (699993)




QUEST 2 LED L - recessed
frame (699986)




QUEST 2 LED L protective grid
RAL7016 (699962)



QUEST 2 LED M protective grid
RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount
RAL7016 (965913)



QUEST 2 LED M/L Pole
holder (567728)