

DEEP

RECESSED PANEL

STH8903BR/30

17W

Power

1400lm

Luminous flux

120°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Beam angle	120°
Luminous efficacy	82lm/W
Power factor	0,92
Luminous flux	1400lm
Frequency	50/60Hz
CRI (Color rendering index)	80
Power	17W
Correlated color temperature (CCT)	3000K
Voltage (V)	100-240V
Voltage (Vac)	100-240Vac
Lifespan	25000h
Register Number	
Certifier Number	
Certifier	

Technical Drawing

STH8903




Graphics

STH8903BR

1m	543lx	2,6m
2m	136lx	5,1m
3m	60lx	7,7m
4m	34lx	10,3m
5m	22lx	12,8m

h, Emax, Ø

STH8903BR



OTHER INFORMATION

Finishing	White
Dimmable	No
Warranty	2 years
Patent information	Patented product
Prevailing material	Polycarbonate

DOWNLOADS

[↓ IES FILE - STH8903BR/30](#)[↓ MANUAL DEEP](#)[↓ SKETCHUP - STELLA - STH8903BR-30-40-50 - STH8903PTO-30-40 - PAINEL DE EMBUTIR RECUADO DEEP 18W_PACK.zip](#)[↓ REVIT - STH8903BR_30_40_50_STH8903PTO_30_40.rfa](#)