


FLAT SLIM round

312644.004.76 | Pendant luminaires



Pendant luminaires
4051859802310
D 400, H 70

pendant
silver, matt (approx. RAL 9006)



Decorative round LED pendant luminaire. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Canopy made of aluminium, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: bayonet system. Uniform lighting achieved by the use of LED panel boards. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. MultiLumen: 2 steps adjustable luminous flux. Factory setting is the highest luminous flux. MultiColour: Colour temperature individually adjustable either 3000 K or 4000 K via switching element. Factory setting is 3000 K. Dimmable DALI.

Product specifications


Diameter D	400 mm
Height H	70 mm
Suspension length LP	500-1500 mm
Weight	5.2 kg
Light source	LED
Colour temperature	3000 K 4000 K
Rated luminous flux	3000 K: 2400 lm 4000 lm 4000 K: 2500 lm 4150 lm
System power	3000 K: 20 W 33 W 4000 K: 20 W 32 W
System efficiency	3000 K: 120 lm/W 121 lm/W 4000 K: 125 lm/W 130 lm/W
Glare evaluation UGR (4H 8H)	3000 K: 21,7 23,5 4000 K: 21,9 23,6
Beam angle	down 131° up 180°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	12
Luminaires on B16A fuse	20
Luminaires on C10A fuse	21
Luminaires on C16A fuse	34
Inrush current / Inrush current duration	21 A / 230 µs
CIE Flux Code / CEN Flux Code	39 70 90 83 100
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature	-25 °C ... + 40 °C
Conformity mark	CE, EAC

FLAT SLIM round

312644.004.76 | Pendant luminaires



Spareparts



982972.002
Replacement LED module



982895.002
Replacement diffuser