

PRODUCT DATASHEET

Decor Perchero Gray

Decor Perchero | Decorative luminaires with hanger and light



Areas of application

- Bedrooms
- Entrance areas
- Offices

Product benefits

- Elegant design
- Soft light thanks to indirect light distribution

Product features

- Possibility to hang up the clothing
- Wall Luminaire
- 3000 K
- Housing material: metal



TECHNICAL DATA

Electrical data


Nominal wattage	12.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	58.000 mA
Inrush current time T_{h50}	1900 μ s
Max. number of luminaires per miniature circuit breaker B16	64
Max. number of luminaires per miniature circuit breaker C16	107
Power factor λ	≥ 0.7
Total harmonic distortion	< 70 %
Protection class	II

Photometrical data

Luminous flux	700 lm
Total luminous flux of contained light sources	1300 lm
Luminous efficacy	58 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0

Dimensions & Weight

Length	770.00 mm
Width	60.00 mm
Height	195.00 mm
Product weight	850.00 g



DECOR PERCHERO GREY

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)




Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR PERCHERO
	Declarations of conformity	DECOR PERCHERO
	Declarations of conformity UKCA	Fixed LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075756847	Folding box 1	76 mm x 232 mm x 420 mm	978.00 g	7.41 dm ³
4058075756854	Shipping box 4	321 mm x 253 mm x 438 mm	4433.00 g	35.57 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.