

EKV1+0 150 VB53TC9 (VB53TC9)

- Anti-rotation crimped cable lugs (type PK1)
- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator

A = 5000 mm



Figure without obligation

Type Part No.	EKV1+0 150 VB53TC9 VB53TC9
Version	Single-pole
Cable cross-section (phase side)	150 mm ²
Cable cross-section (earth side)	150 mm ²
Length of single-pole cable	5000 mm
Cable cross-section	150 mm ²
Fully insulated	No
Max. short-circuit current I _k 0.5 s	42.0 kA
Max. short-circuit current I _k 1 s	29.6 kA
Crimped cable lug	PK1
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	-25 °C ... +55 °C
Material (cable)	E-Cu, extra finely stranded and highly flexible
Material (sheath)	Thermoplastic polymer (flexible PVC compound YM2)
Hole (cable lug)	Ø12.5 mm
Weight	8.23 kg
Customs tariff number	85359000
GTIN	4013364163270
PU	1 Stk

Attention: Please state the relevant Variant No. when ordering.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.