


TRIONA rectangle

312709.002.76 | Surface-mounted luminaires



Ceiling and wall luminaires
4051859965312
L 1300, B 350, H 88

Ceiling mounting, Wall (surface)
traffic white, matt (RAL 9016)



Decorative rectangular LED surface-mounted luminaire. Flat, seamless frame: aluminium extrusion profile, powder coated. Cover made of sheet steel, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. LED backlight technology for homogeneous illumination of the entire light-emitting surface. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. Driver integrated. Dimmable DALI. Suitable for through-wiring.

Product specifications

Length L	1300 mm
Width B	350 mm
Height H	88 mm
Weight	13 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	7400 lm
System power	61 W
System efficiency	121 lm/W
Glare evaluation UGR (4H 8H)	22,7
Beam angle	108°/107°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	80
Colour tolerance	4
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	8
Luminaires on B16A fuse	13
Luminaires on C10A fuse	14
Luminaires on C16A fuse	22
Inrush current / Inrush current duration	53 A / 200 µs
CIE Flux Code / CEN Flux Code	48 79 96 100 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK03
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE