Endurance TPa Recessed Panel














- LED panel suitable for education, commercial and ancillary area applications
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Low glare and even light distribution for multiple applications
- Surface mounting frame option
- Powered by Tridonic
- TPa as standard
- Self-Test Panel Pod and Sensor Pod compatible (see p522 for more information)

















INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220-240V	50-60Hz	-20°C to 40°C	L80 50,000	Ra 80	6	110°	2	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
AERMLED2/120/CW	1200 x 600 - Cool White	60W	4000K	5800lm	96lm	20	£290.00
AERMLED2/120/WW	1200 x 600 - Warm White	60W	3000K	5400lm	89lm	20	£290.00
AERMLED2/120/DL	1200 x 600 - Daylight	60W	6500K	5700lm	94lm	20	£290.00

AIRMLED/POD/3NM/ST	Emergency Pod	5W	£112.00
AIRMLED/POD/MWS	Sensor Pod	1W	£73.00

* UGR Value based on (4H - 8H)

ı	CODE (OPTIONS)	DESCRIPTION	TRADE
	/OCTO	OCTO Smart Control	+ £195.00
	/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AERMLED/120/SMF	1200x600 Surface Mounting Frame	£61.50
APRK/120	1200x600 Plasterboard Recessed Kit	£101.00

