




Pole top luminaires
4051859135654
D 650, H 610

Pole mounting
anthracite metallic (DB703)



Pole-top luminaire in a clear architectural design with modern LED technology. Luminaire body aluminium, arm cast aluminium with integrated wiring and stainless steel threaded inserts (seawater resistant powder-coated). Refractor optics with multichip LED. Aluminium light insert with toughened glazing, powder coated. Asymmetrical light distribution for M lighting classes. Pole attachment for 76 mm spigot. With stainless steel screws. Twist-lock and plug connector for quick replacement. 4 x 1.0 mm² connecting cable included, length 5.5 m. City-Touch-ready, luminaire can be fitted with CityTouch components if required. Please order reducer adapter for pole clamp D 60 mm separately.

Product specifications

Diameter D	650 mm
Height H	610 mm
Weight	14.02 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	5200 lm
System power	65 W
System efficiency	80 lm/W
Glare evaluation UGR (4H 8H)	32
Beam angle	73°/53°/73°/26°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	70
Colour tolerance	5
Photobiological safety according to EN 62471	Risk group 2
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	7
Luminaires on B16A fuse	11
Inrush current / Inrush current duration	65 A / 160 µs
CIE Flux Code / CEN Flux Code	39 76 98 100 100
Type of protection	IP 65
Protection class	II
Filament test	960 °C
Impact resistance	IK07
Ambient temperature	-20 °C ... + 35 °C
Conformity mark	CE, EAC

Accessories



982436.000
Reducing adapter Ø 60 mm



61199.009
Fuse box