


PRODUKTDATENBLATT FX-LFDM -G1-BS-12H13

LINEARlight FLEX® DIFFUSE | – Accessories for side-bending



Anwendungsgebiete

- Architectural Integration – e.g. coves, walls
- Ceiling integration
- Recessed lighting
- Cove lighting
- Shelf and furniture lighting

Produktvorteile


- Kurze Montagezeit (CONNECTsystem)

Produkteigenschaften

- Can be easily combined with covers for homogeneous light distribution
- Clips for easy installation and maintenance
- Compatible with Linearlight Flex
- Ideal even for lighting in confined spaces
- Compatible with TEC Flex


TECHNISCHE DATEN

Maße & Gewicht



Länge	20,0 mm
Breite	13,1 mm
Höhe	12 mm
Produktgewicht	2,4 g

DOWNLOADS

DOWNLOADS	
	User instruction

VERPACKUNGSMITTEL

EAN	Verpackungseinheit (Stück pro Einheit)	Abmessungen (Länge x Breite x Höhe)	Bruttogewicht	Volumen
4052899452541	BAG 1		5.40 g	
4052899452558	Faltschachtel 50	100 mm x 80 mm x 60 mm	323.00 g	0.48 dm ³
4052899452565	Versandschachtel 400	230 mm x 180 mm x 160 mm	2784.00 g	6.62 dm ³

Die genannten Produktnummern beschreiben die kleinste bestellbare Mengeneinheit. Eine Versandeinheit kann mehrere Einzelprodukte beinhalten. Als Bestellmenge verwenden Sie bitte das Ein- oder Mehrfache einer Versandeinheit.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.

