

Product Data Sheet

GWD4229R

90 ReStart Range



Description Automatic reclosing device

Code ReStart Rm 2P

Coupled with GW94229

Rated voltage AC 230 V

Rated current 25 A


Rated current 25 A

No. modules 3

Standard EN 50557

Rated frequency (Hz)	50 - 60 Hz	Distribution system	TT - TN-S
Rated non-operating resistance between live parts and earth (Rdo)	8k Ω	Insulation voltage	500 V
Rated operating resistance between live parts and earth (Rd)	16 k Ω	Rated impulse withstand voltage	4 kV
Maximum operating frequency	30 oper./h	Overvoltage category	III
Mechanical endurance	4000	Dielectric strength test voltage between pole and earth	2500 Vac for 1 minute
Type of residual current protection	A	Rated residual operating current	30 mA
Operating temperature	-5 +40 °C	Stocking temperature	-40 +70 °C
Automatic reclosure for untimely tripping	Yes	Earth failure test	Yes
Continuous system monitoring	No	Number of poles	2P
Curve	C	Type of RCBO	A
Breaking capacity (EN 61009-1)	4500 A	Electrocod	1414
Compatibility with WiFi interface	No		

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 20/04/2023

Data, measures, designs and pictures are shown
only as informative purposes,
and could be changed without previous notice