

# QUEST 2 LED HB M 46300LM I CL. IP66 757 SP10KV (368W)

## DETAILED CARD



## TECHNICAL PARAMETERS

|                                           |           |
|-------------------------------------------|-----------|
| <b>Ingress protection:</b>                | IP66      |
| <b>Impact resistance:</b>                 | IK09      |
| <b>Rated power of the luminaire [W]*:</b> | 368       |
| <b>Luminous flux [lm]*:</b>               | 46300     |
| <b>Colour temperature [K]:</b>            | 5700      |
| <b>Colour rendering index:</b>            | >70       |
| <b>SDCM:</b>                              | ≤ 5       |
| <b>Electrical protection class:</b>       | I         |
| <b>Energy efficiency class:</b>           | D         |
| <b>Material of the body:</b>              | aluminium |

## CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

## APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

# QUEST 2 LED HB M 46300LM I CL. IP66 757 SP10KV (368W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                                |                                                                             |
|-----------------------------------|---------------|--------------------------------|-----------------------------------------------------------------------------|
| Rated power of the luminaire [W]: | 368           | Impact resistance:             | IK09                                                                        |
| Index:                            | 741388        | Ingress protection:            | IP66                                                                        |
| EAN:                              | 5905963741388 | Working temperature [°C]:      | from -20 to +35                                                             |
| Colour temperature [K]:           | 5700          | Version:                       | 2xM                                                                         |
| Luminous flux [lm]:               | 46300         | Lateral surface (SCx) [m2]:    | 0.140                                                                       |
| Beam angle [°]:                   | 120           | Mounting version:              | suspended                                                                   |
| Supply voltage [V]:               | 220 - 240     | Mark D:                        | yes                                                                         |
| Frequency [Hz]:                   | 50 - 60       | Net weight [kg]:               | 8.400                                                                       |
| Luminous efficacy [lm/W]:         | 126           | Warranty [years]:              | 5                                                                           |
| Energy efficiency class:          | D             | Light distribution type:       | symmetric                                                                   |
| Electrical protection class:      | I             | Efficiency of the luminaire:   | 0.93                                                                        |
| Colour rendering index:           | >70           | Additional accessories:        | protective grid                                                             |
| SDCM:                             | ≤ 5           | Photobiological safety:        | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| LED lifespan L70B50 [h]:          | 156000        | Cable length [m]:              | 0.90                                                                        |
| LED lifespan L80B20 [h]:          | 98000         | The number of implement units: | 4                                                                           |
| LED lifespan L90B10 [h]:          | 47000         | Warranty [years]:              | 5                                                                           |
| Surge protection [kV]:            | 10            | CE certificate:                | <a href="#">158/2023</a>                                                    |
| Diffuser material:                | glass         | PZH certificate:               | <a href="#">B-BK-60212-0480/21</a>                                          |
| Diffuser type:                    | transparent   | Manual:                        | <a href="#">Download PDF</a>                                                |
| Material of the body:             | aluminium     | Plik LDT:                      | <a href="#">Download</a>                                                    |
| Colour of the body:               | RAL 7016      |                                |                                                                             |
| Dimensions (H/W/T/S) [mm]:        | 700/450/45    |                                |                                                                             |

# QUEST 2 LED HB M 46300LM I CL. IP66 757 SP10KV (368W)

DETAILED CARD

## ACCESSORIES AVAILABLE


| index  | Name                                                       |
|--------|------------------------------------------------------------|
| 699993 | QUEST 2 LED M - recessed frame                             |
| 699986 | QUEST 2 LED L - recessed frame                             |
| 699948 | QUEST 2 LED HB L protective grid RAL7016 single suspension |
| 699955 | QUEST 2 LED HB M protective grid RAL7016 single suspension |
| 699962 | QUEST 2 LED L protective grid RAL7016                      |
| 699979 | QUEST 2 LED M protective grid RAL7016                      |




QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)