


LEDONA round

901799.002.76 | Recessed downlights



Recessed downlights
4051859918066
D 230, H 3

Recessed ceiling mounting
white



Recessed LED downlight featuring advanced technology and sophisticated design. Housing: die-cast aluminium constructed as heat sink. Bezel ring: die-cast aluminium, powder-coated. Open version. Highly polished four-segment faceted aluminium reflector with light mixing chamber. MultiLumen: Luminous flux adjustable in different steps. Best colour rendering index Ra>90. Installation without tools thanks to spring fastening system. Connected converter included in separate gearbox. With connecting cable (L 250 mm). Suitable for through wiring as standard.

Product specifications

Diameter D	230 mm
Height H	3 mm
Cut-out diameter DA	210 mm
Luminaire: recess height HEL	108 mm
Ceiling thickness S	1-20 mm
Installation space length LE	500 mm
Installation space width BE	500 mm
Installation space height HE	108 mm
Weight	1.76 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1650 lm 2650 lm 3500 lm 4950 lm
System power	12 W 19 W 27 W 41 W
System efficiency	121 lm/W 130 lm/W 138 lm/W 139 lm/W
Glare evaluation UGR (4H 8H)	19,7 21,3 22,3 23,5
Beam angle	90°
Rated life	50000 h (L90/B50)
Colour rendering index (CRI)	92
Colour tolerance	2
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	18
Luminaires on B16A fuse	30
Luminaires on C10A fuse	23
Luminaires on C16A fuse	36
Inrush current / Inrush current duration	50 A / 10 µs
CIE Flux Code / CEN Flux Code	83 100 100 100 100
Type of protection	IP 20 on room side IP 20
Protection class	II
Filament test	850 °C
Impact resistance	IK03
Ambient temperature	5 °C ... + 35 °C
Safety marks	Do not cover the recessed luminaire!
Conformity mark	CE

LEDONA round


901799.002.76 | Recessed downlights



Accessories



982703.002
Through-wiring box



982623.002
refurbishment frames for recessed luminaires