



CALIDO CLICKBEAM maxi D90

742165.002.1 | Surface mounted projector



Surface mounted projectors
4051859740643
D 90, H 162

Track on ceiling
traffic white, matt (RAL 9016)



LED surface-mounted projector with modern cylindrical design with no visible cooling ribs. Housing: die cast aluminium and sheet steel, powder-coated. Track-in driver integrated into the adapter. Rotation range: 356°. Swivel range: 90°. Front ring die-cast aluminium black. Hybrid optical system with polycarbonate lens and reflector in faceted aluminium for particularly homogeneous lighting. Special Click Beam lens suitable for different beam angles. Adjustable lens position by means of push mechanism to adjust the beam angle. Black front ring to prevent glare from the side. UVA- and IR-free light. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Converter integrated in the adapter. The following accessories can be mounted without use of tools: honeycomb louvre.

Product specifications


Diameter D	90 mm
Height H	162 mm
Weight	740 g
Light source	LED
Colour temperature	4000 K
Rated luminous flux	2900 lm 3100 lm
System power	26 W 26 W
System efficiency	112 lm/W 119 lm/W
Glare evaluation UGR (4H 8H)	15,4 18,4
Beam angle	21° 42°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter
Control	on/off
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	10
Luminaires on B16A fuse	12
Luminaires on C10A fuse	15
Luminaires on C16A fuse	25
Inrush current / Inrush current duration	8.7 A / 500 µs
CIE Flux Code / CEN Flux Code	97 100 100 100 100
Type of protection	IP 20
Protection class	I
Filament test	850°C - 30 seconds
Impact resistance	IK03
Ambient temperature	-30 °C ... + 25 °C
Conformity mark	CE

CALIDO CLICKBEAM maxi D90

742165.002.1 | Surface mounted projector



Accessories



982810.003
Anti-glare honeycomb louvre