




Pendant luminaires
4051859999850
L 1012, B 28, H 38

pendant
silver, matt (approx. RAL 9006)



Pendant luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Direct 60%, indirect 40% light emission. Suitable for pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. Converter integrated in the canopy.

Product specifications

Length L	1012 mm
Width B	28 mm
Height H	38 mm
Suspension length LP	100-1500 mm
Weight	1.78 kg
Light source	LED
Colour temperature	#4000 K #4000 K
Rated luminous flux	2300 lm
System power	34 W
System efficiency	68 lm/W
Glare evaluation UGR (4H 8H)	24,7
Beam angle	down 108°/112° up 75°/100°
Rated life	60000 h (L80/B10)
Colour rendering index (CRI)	82
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	11
Luminaires on B16A fuse	18
Luminaires on C10A fuse	19
Luminaires on C16A fuse	31
Inrush current / Inrush current duration	24 A / 275 µs
CIE Flux Code / CEN Flux Code	48 79 96 65 100
Type of protection	IP 20
Protection class	I
Filament test	650 °C
Impact resistance	IK00
Ambient temperature	-25 °C ... + 25 °C
Conformity mark	CE, EAC