
## MEGA CONE 621101.0231.1 | Wall luminaires





Wall luminaires 4051859512165 L 160, B 115, H 249

Wall (surface) anthracite metallic (DB703)



Attractive wall luminaire with innovative housing design and high-quality LED optics. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Luminaire head made of corrosion-resistant pressure die-cast aluminium, powder-coated, with clear glass cylinder and conical reflector. Light emission: downwards. Flood. Switchable separately. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravolock® System. Connection box on base, max. 2 x 5 x 2.5 mm² for loop through.

**Product specifications** 

Product specifications		
Length L	160 mm	
Width B	115 mm	_
Height H	249 mm	
Weight	2.9 kg	
Light source	LED	
Colour temperature	#4000 K   #4000 K	
Rated luminous flux	790 lm	
System power	14 W	
System efficiency	56 lm/W	
Glare evaluation UGR (4H 8H)	22,4	
	down 64°/63°/64°/63°	
Beam angle	up 90°/90°/90°	
Rated life	60000 h (L80/B50)	
Colour rendering index (CRI)	80	
Colour tolerance	3	
Photobiological safety according to EN 62471	Risk group 1	
Driver	Converter	
Control	on/off	
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz	
Luminaires on B10A fuse	39	
Luminaires on B16A fuse	63	
Luminaires on C10A fuse	63	
Luminaires on C16A fuse	100	
Inrush current / Inrush current duration	8 A / 5 μs	
CIE Flux Code / CEN Flux Code	40 72 92 82 100	
Type of protection	IP 65	
Protection class	1	
Filament test	960°C - 30 seconds	
Impact resistance	IK04	
Ambient temperature	-20 °C + 45 °C	
Conformity mark	CE, EAC	

## MEGA CONE 621101.0231.1 | Wall luminaires



## **Spareparts**



982527.0031 Luminaire head, anthracite