



Ledinaire SlimDownlight

DN065C G4 LED20/840 19W 220-240V 8-D225

Ledinaire SlimDownlight, Surface-mounted, 19 W, D225 mm, 2000 lm, 4000 K, Beam angle 110°, White, IP20/40

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information	
Light source replaceable	No
Driver included	Yes
Light source engine type	LED
Lighting Technology	LED
Value ladder	Value
Warranty period	3 years
Light Technical	
Luminous Flux	2,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	105 lm/W
Color rendering index (CRI)	80
Light source color	840 neutral white
Optic type	Beam angle 110°
Luminaire light beam spread	110°
Unified glare rating CEN	28

Photobiological safety according to EN 62471		RG0
Operating and Electrical		
Input Voltage	220 to 240 V	
Line Frequency	50 or 60 Hz	
Input Frequency	50 or 60 Hz	
Inrush current	4.92 A	
Power Consumption	19 W	
Power Factor (Fraction)	0.9	
Connection	Screw connection block 2-pole	
Number of products on MCB of 16 A type B	55	
Protection class IEC	Safety class II	
Total harmonic distortion	30 %	
Controls and Dimming		
Dimmable	No	
Driver/power unit/transformer	Power supply unit (On/Off)	

Ledinaire SlimDownlight

Constant light output	No
-----------------------	----

Mechanical and Housing	
Housing Material	Metal–Plastic
Reflector material	-
Housing Color	White
Overall length	225 mm
Overall width	225 mm
Overall height	27 mm
Overall diameter	225 mm
Dimensions (Height x Width x Depth)	27 x 225 x 225 mm
Ingress protection code	IP20/40 [Finger-protected;Wire-protected]
Mech. impact protection code	IK03 [0.3 J]
Net Weight (Piece)	0.580 kg

Approval and Application

Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	0.7
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5


Over Time Performance (IEC Compliant)

Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L65
---	-----


Product Data

Order product name	DN065C G4 LED20/840 19W 220-240V 8-D225
Full product name	DN065C G4 LED20/840 19W 220-240V 8-D225
Full product code	871951446453700
Order code	929003251832
Material Nr. (12NC)	929003251832
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514464537
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514464544


Dimensional drawing



Photometric data



Light Distribution Diagram - DN065C G4 LED20/840 19W 220-240V 8-D225



General uniform lighting - DN065C G4 LED20/840 19W 220-240V 8-D225

