

S.GROUND

LED INGROUND WITH ANTI-GLARE GRID

STL23719/30



18,5W

Power

1120lm

Luminous flux

14°

Beam angle




TECHNICAL SPECIFICATIONS TABLE

Lifespan	25000h
Voltage (Vac)	100-240Vac
Voltage (V)	100-240V
Correlated color temperature (CCT)	3000K
Power	18,5W
Luminous intensity	12500cd
CRI (Color rendering index)	80
Ingress protection rating (IP)	IP67
Frequency	50/60Hz
Luminous flux	1120lm
Power factor	0,92
Luminous efficacy	60lm/W
Beam angle	14°

Technical Drawing

STL23719




Graphics

STL23719

1m	13320lx	0,3m
2m	3330lx	0,5m
3m	1480lx	0,8m
4m	832lx	1,1m
5m	533lx	1,3m

h, Emax, Ø

STL23719



— C0/180 — C90/270

OTHER INFORMATION

Prevailing material	Aluminum
Patent information	Patented product
Warranty	2 years
Dimmable	No
Color temperature	Warm white
Finishing	Black

DOWNLOADS

[↓ IES FILE - STL23719/30](#)
[↓ MANUAL S.Ground](#)
[↓ SKETCHUP - STELLA - STL23719-30 - EMBUTIDO DE SOLO GROUND 20W COM GRADE_PACK.zip](#)
[↓ REVIT - STL23719_30.rfa](#)
