



CorePro LED PLC 2P

CorePro LED PLC 6.5W 840 2P G24d-2

CorePro LED PLC 2P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

Product data

General Information	
Cap-Base	G24D-2 [G24d-2]
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	700 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	92.31 lm/W
Color Consistency	<6
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Starting Time (Nom)	0.5 s

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Temperature	
Ambient temperature range	-20 °C to 35 °C
T-Case Maximum (Nom)	65 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Material	Plastic
Product Length	100 mm
Bulb Shape	Tube, single-ended
Approval and Application	
Energy Saving Product	Yes
Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	403,557
CE mark	Yes

CorePro LED PLC 2P

EU RoHS compliant	Yes
Product Data	
Full product code	871869654129600
Order product name	CorePro LED PLC 6.5W 840 2P G24d-2
Order code	929001201502
Numerator - Quantity Per Pack	1



Numerator - Packs per outer box	10
Material number (12NC)	929001201502
Full product name	CorePro LED PLC 6.5W 840 2P G24d-2
EAN/UPC - Case	8718696541302

Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 840 2P G24d-2	24.3 mm	28.4 mm	105.8 mm	125 mm	147.6 mm

Photometric data





Spectral Power Distribution Colour - CorePro LED PLC 6.5W 840 2P G24d-2



Light Distribution Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



CorePro LED PLC 2P

Lifetime




Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Life Expectancy Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2



Lumen Maintenance Diagram - CorePro LED PLC 6.5W 840 2P G24d-2

CorePro LED PLC 2P

