

## S.GROUND

LED INGROUND

STL23709/30



18,5W

Power

1500lm

Luminous flux

36°

Beam angle




## TECHNICAL SPECIFICATIONS TABLE

|                                    |            |
|------------------------------------|------------|
| Lifespan                           | 25000h     |
| Voltage (Vac)                      | 100-240Vac |
| Voltage (V)                        | 100-240V   |
| Correlated color temperature (CCT) | 3000K      |
| Power                              | 18,5W      |
| Luminous intensity                 | 3800cd     |
| CRI (Color rendering index)        | 80         |
| Ingress protection rating (IP)     | IP67       |
| Frequency                          | 50/60Hz    |
| Luminous flux                      | 1500lm     |
| Power factor                       | 0,92       |
| Luminous efficacy                  | 81lm/W     |
| Beam angle                         | 36°        |

## Technical Drawing

STL23709




## Graphics

STL23709

|    |        |      |
|----|--------|------|
| 1m | 3964lx | 0,7m |
| 2m | 991lx  | 1,5m |
| 3m | 440lx  | 2,2m |
| 4m | 248lx  | 2,9m |
| 5m | 159lx  | 3,6m |

h, Emax, Ø

STL23709



## OTHER INFORMATION

|                     |                  |
|---------------------|------------------|
| Prevailing material | Aluminum         |
| Patent information  | Patented product |
| Warranty            | 2 years          |
| Dimmable            | No               |
| Color temperature   | Warm white       |
| Finishing           | Black            |

## DOWNLOADS

[↓ IES FILE - STL23709/30](#)
[↓ MANUAL S.Ground](#)
[↓ SKETCHUP - STELLA - STL23709-30 - EMBUTIDO DE SOLO GROUND 20W SEM GRADE\\_PACK.zip](#)
[↓ REVIT - STL23709\\_30.rfa](#)
