

Ewon Flexy extension card - WiFi

Item number: FLB3271_00

This extension card enhances Ewon Flexy's connectivity with a WiFi modem. More and more WLAN (WiFi) access points are available in the industry. They allow connectivity while avoiding connection on the factory LAN network. Powerful backup Internet access for industrial M2M applications. Compatible with Ewon Flexy 10x, 20x series and 205.



Interchangeable extension card for enhanced connectivity

Features and benefits

Build your own Flexy gateway

Keep up with the evolution of communication technologies while protecting your investment in the device! The Ewon Flexy extension cards make this gateway highly modular and flexible.







| Net Width (mm) | 22 |
|------------------------------|---|
| Net Height (mm) | 79 |
| Net Depth (mm) | 82 |
| Net Weight (g) | 53 |
| Packed Width (mm) | 102 |
| Packed Height (mm) | 30 |
| Packed Depth (mm) | 95 |
| Packed Weight (g) | 74.5 |
| Operating Temperature °C Min | -25 |
| Operating Temperature °C Max | +60 |
| Storage Temperature °C Min | -30 |
| Storage Temperature °C Max | +70 |
| Relative Humidity | 10 to 95% relative humidity (non-condensing). |
| Content of Delivery | This product consists of the following components: an electronic extension board inserted in a plastic front plate and packed in an ESD plastic bag sealed with an yellow sticker, a WIFI antenna, legal references in paper version and a cardboard box. |
| Not Included (in delivery) | WIFI extended cable |
| Housing Materials | Plastic |
| Packaging Material | Cardboard |
| Warranty (years) | 3 |

Identification and Status

| Product ID | FLB3271_00 |
|------------|------------|







Identification and Status Model Code 01201 Country of Origin Belgium HS Code 8517790000 Export Control Classification

Physical Features

Number (ECCN)

Connectors / Input / Output 1x Antenna connector: RP-SMA female connector

5A992.c

Wireless Features

| Antenna Connector | RP-SMA |
|---------------------|---|
| Antenna | Included |
| Wifi Standards | IEEE versions: 802.11 b/g/n, Single stream |
| Cellular Standards | Our Modem Flexy Extension Cards FLB3208, FLB320A, FLB3209, FLB3271 are only supported if the Flexy Base Unit runs the firmware version 14.8s0 and higher. |
| Frequencies & Bands | Channels: 1 to 11 (inclusive) |

Certifications and Standards

| Environment | Temperature - Operating & Storage tested according to: IEC 60068-2-1 Cold test, IEC 60068-2-2 Dry heat test, IEC 60068-2-14 Change of temperature, IEC 60068-2-30 Cyclic damp heat test |
|---------------------|---|
| Vibration and Shock | Vibration & shocks tested according to: IEC 60068-2-27 Bumps, IEC 60068-2-64 Vibration (broad-band random), IEC 60068-2-6 Vibration (sinusoidal) |
| WEEE Category | IT and telecommunications equipment |
| Other Certification | Giteki Japan, Russia FSS Notification, WPC India, Pakistan |

