DEECOS S mini track-in


742258.004.730 | Surface mounted projector





Surface mounted projectors 4051859814566 D 87, H 135

Track on ceiling, Wall track silver



LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. Track-in driver integrated into the adapter. High quality converter without flickering and stroboscopic effect. With Casambi smart+free Bluetooth® control for wireless network and operation using Android / iOS devices, free app available for download. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

Product specifications

| Product specifications | | |
|--|--------------------------|--|
| Diameter D | 87 mm | |
| Height H | 135 mm | |
| Weight | 0.62 kg | |
| Light source | LED | |
| Colour temperature | 3000 K | |
| Rated luminous flux | 3550 lm | |
| System power | 29 W | |
| System efficiency | 122 lm/W | |
| Glare evaluation UGR (4H 8H) | 15,2 | |
| Beam angle | 18° | |
| Rated life | 50000 h (L90/B10) | |
| Colour rendering index (CRI) | 92 | |
| Colour tolerance | 2 | |
| Photobiological safety according to EN 62471 | Risk group 1 | |
| Driver | Converter, dimmable | |
| Control | smart+free (Bluetooth) | |
| Voltage | 220 - 240 V / 50 - 60 Hz | |
| Luminaires on B10A fuse | 17 | |
| Luminaires on B16A fuse | 27 | |
| Luminaires on C10A fuse | 28 | |
| Luminaires on C16A fuse | 44 | |
| Inrush current / Inrush current duration | 18 A / 2 μs | |
| CIE Flux Code / CEN Flux Code | 100 100 100 100 | |
| Type of protection | IP 20 | |
| Protection class | II | |
| Filament test | 650°C - 30 seconds | |
| Impact resistance | IK06 | |
| Ambient temperature | 25 °C | |
| Conformity mark | CE, EAC | |

DEECOS S mini track-in

742258.004.730 | Surface mounted projector



Accessories



982370.000 Diffuser, transparent



982371.003 Anti-glare honeycomb louvre



982369.013 Medium lens



982421.002 White plastic ring for lens.



982368.013 Reflector medium



982369.033 Wide flood lens



982419.002 White plastic ring for reflector.



982647.002 Decorative glass opal matt



982370.010 Diffuser, satinated



982369.003 Spot lens



982369.023 Flood lens



982368.003 Reflector spot



982368.023 Reflector flood



982369.043 Oval corridor lens



982368.033 Reflector wide flood



982648.002 Decorative glass opal matt