

QUEST 2 LED HB NT L 20100LM DALI I CL. IP66 840 SP10KV (145W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	145
Luminous flux [lm]*:	20100
Colour temperature [K]:	4000
Colour rendering index:	> 80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	C
Material of the body:	aluminium

CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

QUEST 2 LED HB NT L 20100LM DALI I CL. IP66 840 SP10KV (145W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	145	Ingress protection:	IP66
Index:	698545	DIMM DALI:	yes
Colour temperature [K]:	4000	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	20100	Version:	1xL
Beam angle [°]:	120	Lateral surface (SCx) [m2]:	0.180
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Mark D:	yes
Luminous efficacy [lm/W]:	139	Net weight [kg]:	5.200
Energy efficiency class:	C	Warranty [years]:	5
Electrical protection class:	I	Light distribution type:	symmetric
Colour rendering index:	> 80	Efficiency of the luminaire:	0.96
SDCM:	≤ 3	Additional accessories:	protective grid
LED lifespan L70B50 [h]:	125000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L80B20 [h]:	79000	Cable length [m]:	0.90
LED lifespan L90B10 [h]:	38000	The number of implement units:	1
Surge protection [kV]:	10	Warranty [years]:	5
Diffuser material:	glass	CE certificate:	158/2023
Diffuser type:	transparent	PZH certificate:	B-BK-60212-0480/21
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	anthracite grey	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	415/424/37		
Impact resistance:	IK09		

QUEST 2 LED HB NT L 20100LM DALI I CL. IP66 840 SP10KV (145W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699948	QUEST 2 LED HB L protective grid RAL7016 single suspension
699955	QUEST 2 LED HB M protective grid RAL7016 single suspension
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016



QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)