



CorePro GLASS LED candles and lusters

CorePro LEDCandleND6.5-60W B35 E14840CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap-Base	E14
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	55 °C
Controls and Dimming	
Dimmable	No

CorePro GLASS LED candles and lusters

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	B35
Net Weight (Piece)	0.012 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825172
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9


Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

Product Data



Order product name	CorePro LEDCandleND6.5-60W B35 E14840CLG
Full product name	CorePro LEDCandleND6.5-60W B35 E14840CLG
Full product code	871951434748900
Order code	929002028192
Material Nr. (12NC)	929002028192
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347489
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347496

Dimensional drawing



Product	D	C
CorePro LEDCandleND6.5-60W B35 E14840CLG	35 mm	97 mm

Photometric data




General uniform lighting - CorePro LEDCandleND6.5-60W B35 E14840CLG

Light Distribution Diagram - CorePro LEDCandleND6.5-60W B35 E14840CLG


CorePro GLASS LED candles and lusters

Photometric data




Spectral Power Distribution Colour - CorePro LEDCandleND6.5-60W B35
E14840CLG

Lifetime



Lumen Maintenance Diagram - CorePro LEDCandleND6.5-60W B35
E14840CLG



Life Expectancy Diagram

