



Ledinaire Waterproof WT065C

WT065C LED29_48S/840 PSU L1200 TW1

Ledinaire Waterproof WT065C, All-in, 42 W, 23 W, L1200 mm, 2900 lm, 4800 lm, 4000 K, Symmetrical, Opal, IP65, IK08, TW1

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	No
Lighting Technology	LED
Value ladder	Value
Warranty period	3 years
Sustainability rating	-
Light Technical	
Luminous Flux	2,900 4,800 lm
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	126 114 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optic type	Symmetrical

Luminaire light beam spread	110°
Unified glare rating CEN	31
All-in Type	All-in, Multi Lumen
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	14.2 A
Inrush time	0.222 ms
Power Consumption	42 23 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 3-pole
Cable	-
Number of products on MCB of 16 A type B	36
Suitable for random switching	No
Protection class IEC	Safety class I
Feed-through wiring	Feed-through wiring 1-phase

Ledinaire Waterproof WT065C

Total harmonic distortion	12 %
---------------------------	------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Grey
Optical cover finish	Opal
Overall length	1,214 mm
Overall width	71 mm
Overall height	74 mm
Dimensions (Height x Width x Depth)	74 x 71 x 1214 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Net Weight (Piece)	1.300 kg

Emergency Operation

Central Emergency	No
-------------------	----

Approval and Application

Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on easily flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.38) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5


Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L70
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	-

Product Data

Order product name	WT065C LED29_48S/840 PSU L1200 TW1
Full product name	WT065C LED29_48S/840 PSU L1200 TW1
Full product code	872016950023599
Order code	911401815385
Material Nr. (12NC)	911401815385
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169500235
Numerator - Packs per outer box	9
EAN/UPC - Case	8720169500334

Dimensional drawing



Ledinaire Waterproof WT065C

